

# Tutorial

## Table des matières

1. What for?.....	2
2. Installation & configuration.....	2
2.1. File sharing platform.....	2
2.2. Server of instances.....	3
3. First steps.....	4
3.1. Lock a folder.....	4
3.2. Rename, Move or Delete a folder.....	4
3.3. Information message.....	4
3.4. File format filtering.....	4
3.5. Notebook & Notification.....	4
3.6. Links.....	5
3.7. Special files.....	5
4. Advanced management.....	5
4.1. Time-stamped folder.....	5
4.2. Invisible folder.....	5
4.3. Log of IP@.....	5
4.4. Anonymous login.....	5
4.5. Recovery of admin rights.....	6
5. The toolbar.....	6

QDRep, a free software solution for files exchange.

<https://linuxfr.org/news/qdrep-une-solution-libre-pour-l-echange-de-fichiers>



## 1. What for?

QDRep is a Free file sharing software. Here are some criteria that may decide whether to use it (or not).



Lightweight (~2000 lines of code)

Easy to install (paste 'n' play)

No database

Direct sharing by URL

Libre and free

GDPR compatible

Responsive (ie: usable on SMART)

Available in 6 languages

With or without anonymous connection



Requires PHP 5+

Low security over file access

Limited uploading to 3 or 5 MB / file<sup>1</sup>

## 2. Installation & configuration

QDRep can be installed in two different ways:

### 2.1. File sharing platform

[Download](#) the zip, open the "src" folder, then copy the **index.php** file and the **.data** folder to where the host should point (ie: the QDRep root folder).

Edit the **.data/config.php** file to configure QDRep according to your needs. Here are the main parameters:

- `$LANG = "en";`

The language of the interface. Other languages are available in the **.data/msg** folder.

- `$ROOT = "/";`

The QDRep installation root folder (by default, directly at the server base).

- `$KEY = "keepyoursecretsecret";`

The IP@ encryption key.

- `$PORT = 80;`

The http port (default 80).

- `$PASSWD = Array("127.0.0.1");`

The list of IP@s with extended administrator rights. The \* character gives these rights to any connection on the platform (useful for a sandbox for example).

Edit the **./data/msg/fr.php** file to customize your site:

- `$MSG_TITLE = "Computer Science";`

<sup>1</sup> Depends of server configuration

- `$MSG_SUBTITLE = "Free and Open Educational Resources ";`

## 2.2. Server of instances

A server of instances is useful if you need to run QDRep under multiple accounts (ie: multiple users). If it is only for your personal use, jump to the next chapter.

[Download](#) the zip file, then copy the **index.php** file and the **src** folder to where the host should point (ie: the QDRep root folder).

The screenshot shows the QDRep configuration interface. At the top left is the 'QDRep' logo, and at the top right are flags for the UK and France, with the text 'Take a look at the [documentation](#).' Below this is a form with the following fields:

- Title:** A text input field containing 'Computing & Digital Science'.
- Subtitle:** A text input field containing 'Free and Open Educational Resources'.
- Root directory:** A text input field containing '/src/'.
- My Instances:** A dropdown menu showing '--- 4 ---'.
- http port:** A text input field containing '80'.
- admin IP:** A text input field containing '78.231.60.1'.
- Encryption key:** A text input field containing 'keepyoursecretsecret'.
- Password:** A text input field with 10 dots representing a masked password.

At the bottom of the form is a large blue button labeled 'Envoyer'.

The default instance is **src**; accessible for example by <http://mysite.eu.org/src>.

Each instance is specifically configurable as shown in the screenshot above.

The fields to be filled in correspond to the configuration parameters described in the previous section "File sharing platform".

Edit the **.data/config.php** file to configure the server password.



- `$INSTANCE = "keepyoursecretsecret";`


### 3. First steps

Once unzipped and configured, QDRep is immediately usable.

#### 3.1. Lock a folder

Prevents users from downloading a file or creating a folder.

- if icon  is not visible, you do not have administrator rights.
- if icon  appears, the folder is not writable.



#### 3.2. Rename, Move or Delete a folder

The deletion is recursive (ie: deletes the tree structure of a folder).

#### 3.3. Information message

Create a **.readme** text file, and then upload it to the desired folder on the platform.

This file can be interpreted in html.

To delete the message, click on the cross on the border.

#### 3.4. File format filtering

QDRep has 2 types of filters:

- filters to reject file formats: **.reject** text file.
- filters to accept file formats: **.allow** text file.

Create the desired filter, then upload it to the considered folder.

These files must contain the name of the extensions separated by a dot.

It is possible to specify a maximum size (in kB) on the files to upload by adding it at the end of the file, separated by ':'.

Example of **.reject** filter: **.png.php.js** (reject extension files **.png**, **.php** or **.js**)

Example of **.allow** filter: **.pdf: 100** (only accepts pdf files  $\leq$  100 kB).

To view and delete a filter, click on 

#### 3.5. Notebook & Notification

QDRep has a special **.notebook** file for quick and easy communication with participants.


To create it, simply upload it and then click on the link to edit its content online.

the notebook is marked with the icon 

It is possible to notify the modifications made to the notebook with the special file **.notify**.

This file must include the list of emails, separated by a comma, of the persons to be notified.

The notification file is encrypted.

To modify the list of emails, click on the icon . If this list is empty, the **.notify** file will be automatically deleted.

### 3.6. Links

QDRep also allows you to save links to other resources.

To do this, just copy and paste the URL into the input area below.

### 3.7. Special files


As you have seen, QDRep has 5 special files: `.allow`, `.reject`, `.readme` and `.notebook`.

You can upload them via the standard interface or create them directly online by entering their names in the "new folder | URL" entry field.


## 4. Advanced management

### 4.1. Time-stamped folder

A time-stamped folder remains accessible in writing (upload) only for a limited time (1 hour by default).

1. A time-stamped folder begins with the `@` character (the folder is designated by )
2. Unlock the folder, the countdown is immediately started as soon as the folder is unlocked.  
The countdown is in seconds and is displayed in red color, 5 min before the end.
3. At the end of the countdown, the folder automatically switches back to lockout.

The icon  shows a time-stamped folder being counted.

NB: to set the timer, click on 

### 4.2. Invisible folder

It is sometimes necessary to give deferred access to a specific folder. For this, it must be invisible to Internet users who do not have extended privileges (ie: admin).

An invisible folder begins with the `$` character.

To make it accessible later, you have to rename it and remove the `$` character.

### 4.3. Log of IP@

For maintenance and security reasons, the IP@s of the uploaded files are saved. These are only visible to the administrator.

IP@s are encrypted, this feature can be disabled in the `.data/config.php` file if you set the `$PRIVACY` variable to 0.

### 4.4. Anonymous login

QDRep allows anonymous connections by default.

However, it is possible to set up an identification by setting, in the `.data/config.php` file, the variable `$PRIVACY` to 2.

At this moment, a connection button appears at the bottom right of the page that invites the user to give:

- his name
- his password
- and, optionally, his email to receive notifications from the notebook



the green button invites the internaut to identify

An anonymous connection will then no longer be able to deposit documents on the platform.

#### 4.5. Recovery of admin rights

If your IP address has changed, you will lose admin rights (unless the character \* has been used).

To recover these rights, update the **.data/config.php** file by giving the parameter **?recover** in the url of the platform.

Ex: <http://mysite.eu.org/?recover>

To validate the modification, it will be necessary to give the password of the encryption key.

### 5. The toolbar

QDRep has a shortcut bar accessible from the documents icon.

..	
2D3	26/Apr/2020 11:48
	26/Apr/2020 11:48
2D5	26/Apr/2020 11:48
2D6	26/Apr/2020 11:49
2D8	26/Apr/2020 11:49

: permanent deletion of the folder or file.

: recursive locking of folders and subfolders.

: (un)locking of the backrest.

: makes the folder or file (in)visible.

: move the folder or file to the bin.

: allows to rename and/or move a folder or a file.

: download the folder in zip format.

NB: only the last 3 options are available outside of administrator rights provided that the current folder is not locked.